



# ASCD 18-300 W2 AS

## Cordless Impact Wrench

Up to max. 214 ft/lb with brushless motor and 6 torque settings. For screw applications up to 11/16 in [M18].

Product number: 7 115 10 61 09 0

### Details

- + Extreme precision: the ASCD 18-300 W2 AS with 6 electronic torque settings.
- + The VARIO adapter expands the range of the impact wrench to include drilling, countersinking, and tapping.
- + Brushless FEIN PowerDrive motor with 30% greater efficiency and longer service life.
- + 1/2" square drive for mounting impact sockets.
- + 10% higher torque in reverse.
- + Robust, solid metal impact gearbox.
- + Up to 600 fastening applications 11/16 in with one battery charge (CORE 18 V 4 Ah).
- + Compact design.
- + Comes with a magnetic bit holder and belt clip.
- + Compatible with all CORE 18 V AMPShare batteries and chargers, for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless tools.
- + COOLPACK 2.0 technology ensures a 135% longer battery service life, enabling longer operation time.
- + State-of-the-art cell technology and intelligent battery management deliver 87% more power than conventional batteries.
- + CORE 18 V Li-ion battery with Highpower cells, charge indicator and electronic cell protection (ECP). ECP protects batteries against overloading, overheating and deep discharge.
- + Perfectly equipped for any job with our L-BOXX system.

### Price includes

- + 1 belt clip
- + 1 magnetic bit holder
- + 1 tool case (L-BOXX 136)

### Technical data

#### TECHNICAL DATA

Battery voltage

18 V

Battery compatibility

Li-ion / CORE 18 V Li-

#### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA  
Measurement uncertainty of the measured value KpA

99,2 dB  
3 dB



# FEIN

	ions		
Battery interface	18 V AMPShare	Sound power level LWA Measurement uncertainty of the measured value KWA	107,2 dB 3 dB
Motor	brushless	Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	121,5 dB 3 dB
No load speed	0 - 1700 rpm		
Impacts per minute	0 - 3400 rpm	Vibration value 1 $\alpha_{hv}$ 3-way	$\alpha_h$ 15,0 m/s <sup>2</sup>
Max. torque	2567 [290] in/lbs[Nm]	Measurement uncertainty of the measured value K $\alpha$	1,5 m/s <sup>2</sup>
Max. torque	214 ft/lb		
Torque steps	6		
Tool mount	1/2" square		
Max. bolt	11/16 in [M18]		
Weight without battery	2.65 [1.20] lbs[kg]		

## Application examples

**AMPShare**  
Powered by **BOSCH**

Compatible with AMPShare/Bosch Professional 18 V batteries. |  
Compatible avec les batteries 18 V AMPShare/Bosch Professional. |  
Compatible con baterias AMPShare/Bosch Professional de 18 V.

