



ASCD 18-1000 W34 AS

Cordless Impact Wrench

Up to max. 775 ft/lb with brushless motor and 6 torque settings. For fastening applications up to 1-1/16 in [M 27].

Product number: 7 115 12 61 09 0

Details

- + Extreme precision: the ASCD 18-1000 W34 AS with 6 electronic torque settings.
- + The VARIO adapter expands the range of the impact wrench to include drilling, countersinking, and tapping.
- + Brushless FEIN PowerDrive motor with 30% greater efficiency and longer service life.
- + 3/4" external square for mounting impact sockets.
- + High torque up to 775 ft/lb for tightening and 1,105 ft/lb loosening screws up to 1-1/16 in [M 27].
- + Robust, solid metal impact gearbox.
- + Up to 600 fastening applications 1-1/16 in [M 27] with one battery charge (CORE 18 V 8 Ah).
- + Compatible with Bosch Professional 18 V storage batteries since 2008 and AMPShare storage batteries.
- + COOLPACK 2.0 technology ensures a 135% longer battery service life, enabling longer operation time.
- + State-of-the-art cell technology and intelligent battery management deliver 87% more power than conventional batteries.
- + CORE 18 V Li-ion battery with Highpower cells, charge indicator and electronic cell protection (ECP). ECP protects batteries against overloading, overheating and deep discharge.
- + Perfectly equipped for any job with our L-BOXX system.

Price includes

- + 1 tool case (L-BOXX 136)

Technical data

TECHNICAL DATA

Battery voltage

18 V

Battery compatibility

Li-ion / CORE 18 V Li-ions

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Measurement uncertainty of the measured value KpA

96,7 dB
3 dB

Sound power level LWA
Measurement uncertainty of the

104,7 dB



Battery interface	18 V AMPShare	measured value KWA	3 dB
Motor	brushless	Peak sound value LpCpeak	121,3 dB
No load speed	0 - 1 800 rpm	Measurement uncertainty of the measured value KpCpeak	3 dB
Impacts per minute	0 - 2 200 rpm	Vibration value 1 α_{hv} 3- way	ah 15,7 m/s ²
Max. torque	9293 [1,050] in/lbs[Nm]	Measurement uncertainty of the measured value K α	1,5 m/s ²
Max. torque	775 ft/lb		
Torque steps	6		
Tool mount	3/4" Outer square		
Max. bolt	1-1/16 in [M 27]		
Wood screw dia.	1/2 [12] x 23-5/8 [600] in[mm]		
Weight without battery	6.83 [3.10] lbs[kg]		

Application examples



Compatible with
AMPShare/Bosch
Professional
18 V batteries. |

Compatible avec les batteries 18 V
AMPShare/Bosch Professional. |
Compatible con baterías AMPShare/
Bosch Professional de 18 V.



