

SAFETY DATA SHEET

Prepared according to USA OSHA Hazcom 2012 / Canada WHMIS 2015



Date Issued : 03/04/2019
SDS No : SSGC Spray Gun Paint Remover 425g_EN
Date Revised : 07/14/2020
Revision No : 4

SSGC SPRAY GUN PAINT REMOVER, aerosol

1. IDENTIFICATION

Product Name: SSGC SPRAY GUN PAINT REMOVER, aerosol
Product Description: Paint Stripper, aerosol 425 g / 15 oz
General Use: Paint Stripper
Product Stock/Code: SSGC / 10065
Chemical Family: Solvent-based
Molecular Formula: Mixture

Manufacturer / Supplier

Dominion Sure Seal Ltd.
6175 Danville Road, Mississauga
Ontario, Canada L5T 2H7
Fax: 905-670-5174
www.dominionsureseal.com

Customer Service: 905-670-5411

Emergency Telephone Numbers (24 hour)

CANUTEC : (613) 996-6666
CHEMTREC : (800) 424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

The classification and label elements stated below were prepared in accordance with the USA OSHA Hazard Communication Standard (29 CFR 1910.1200; Hazcom 2012) and the Canadian WHMIS regulations (Hazardous Products Regulations; WHMIS 2015). This information may be different from the actual product label information for labels that are regulated by other agencies.

Health hazards:

Acute Toxicity (Oral and Inhalation), Category 4
Specific Target Organ Toxicity (Single exposure), Category 1
Eye Irritation, Category 2
Specific Target Organ Toxicity (Single exposure), Category 3 (Narcotic Effects)
Specific Target Organ Toxicity (Repeated exposure), Category 2
Carcinogenicity, Category 2

Physical hazards:

Flammable Aerosols, Category 1
Gases Under Pressure
Simple Asphyxiants, Category 1

Label elements

Hazardous components for labelling:

acetone, methanol, 2-(2-ethoxyethoxy)ethanol, methyl ethyl ketone, light aromatic solvent naphtha (petroleum), 2-methoxy-1-methylethyl acetate, xylene, mixed isomers and ethylbenzene



Flame



Gas
cylinder



Exclamation
mark



Health
hazard

Signal Word: DANGER

Hazard statement(s)

- H222: Extremely flammable aerosol.
- H280: Contains gas under pressure; may explode if heated.
- H302 + H332: Harmful if swallowed or if inhaled.
- H370: Causes damage to eyes and optic nerve.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H373: May cause damage to hearing organs and central nervous system through prolonged or repeated exposure.
- H351: Suspected of causing cancer.
- H600: May displace oxygen and cause rapid suffocation.

Precautionary statement(s)

Prevention:

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211: Do not spray on an open flame or other ignition source.
- P251: Pressurized container: Do not pierce or burn, even after use.
- P260: Do not breathe mist, vapours or spray.
- P271: Use only outdoors or in a well-ventilated area.
- P280: Wear protective gloves, protective clothing and eye protection.
- P264: Wash hands and exposed skin thoroughly after handling.
- P270: Do not eat, drink or smoke when using this product.

Response:

- P308+P313: IF exposed or concerned: Get medical advice/ attention.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312: Call a POISON CENTER or doctor/physician if you feel unwell.
- P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- P330: Rinse mouth.
- P331: Do NOT induce vomiting.

Storage:

- P403+P233: Store in a well-ventilated place. Keep container tightly closed.
- P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P405: Store locked up.

Disposal:

- P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

Hazards Not Otherwise Classified: Aspiration hazard - Category 2 May be harmful if swallowed and enters airways.

Emergency Overview

Immediate concerns: Extremely flammable aerosol. May cause damage to eyes and optic nerve. May cause blindness if swallowed. May be harmful if inhaled. Causes serious eye irritation. Vapours may cause drowsiness

SSGC SPRAY GUN PAINT REMOVER, aerosol

and dizziness. Prolonged or repeated exposure may cause nervous system damage. Suspected of causing cancer. Vapor reduces oxygen availability for breathing.

Comments: < 5 % of the mixture consists of an ingredient or ingredients of unknown acute toxicity.
See sections 9 and 10 for more detailed information on physicochemical effects.
See section 11 for more detailed information on health effects.
See sections 12 for more detailed information on environmental effects.

The actual container label may not include the above label elements. The labeling shown above applies to products used solely for industrial / professional use.

Consumer products should be labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations. Consumer product labeling takes precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | Wt.% | CAS number |
|--|-------------|------------|
| acetone | 50 - 51 | 67-64-1 |
| propane | 13.5 - 14.5 | 74-98-6 |
| methanol | 10.5 - 11.5 | 67-56-1 |
| isobutane | 5.5 - 6.5 | 75-28-5 |
| 2-(2-ethoxyethoxy)ethanol | 4.5 - 5.5 | 111-90-0 |
| methyl ethyl ketone | 3 - 4 | 78-93-3 |
| light aromatic solvent naphtha (petroleum) | 3 - 4 | 64742-95-6 |
| 2-methoxy-1-methylethyl acetate | 3 - 4 | 108-65-6 |
| xylene, mixed isomers | 2.2 - 2.6 | 1330-20-7 |
| ethylbenzene | 0.5 - 0.7 | 100-41-4 |
| cumene | < 0.1 | 98-82-8 |

Comments: There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.
light aromatic solvent naphtha (petroleum) is a complex substance i.e. complex mixture of known or unknown composition. cumene and ethylbenzene are hazardous constituents that may be contained in the complex substance at 1 to 2% w/w for cumene and at 0.1 to 0.5% w/w for ethylbenzene.
xylene, mixed isomers is a complex substance i.e. complex mixture of known or unknown composition.
ethylbenzene is a hazardous constituent that may be contained in the complex substance at 18 to 20% w/w.

4. FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Get medical attention, if irritation persists.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

Ingestion: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Signs and Symptoms of Overexposure

Eye Contact: Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Skin Contact: Prolonged or repeated contact may cause skin irritation. May be absorbed through the skin in

SSGC SPRAY GUN PAINT REMOVER, aerosol

harmful amounts. Vapor inhalation and/or skin absorption can cause central nervous system effects and blindness.

Ingestion: May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea. Poison, May be fatal or cause blindness if swallowed.

Inhalation: High vapor or spray mist concentrations may be harmful if inhaled. May cause headaches and dizziness. High vapor concentrations may cause drowsiness. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness). High vapor concentrations can displace oxygen in enclosed spaces and cause asphyxiation.

Notes to Physician: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

Additional Information: No data available.

5. FIRE FIGHTING MEASURES

Flammable Properties: Extremely flammable aerosol. Can readily form explosive mixtures at or above the flash point.

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Hazardous Combustion Products: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Fire Fighting Procedures: Containers can build up pressure if exposed to heat (fire).

Fire Fighting Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

Sensitivity to Static Discharge: Product is sensitive to static discharge.

Sensitivity to Mechanical Impact: Product is sensitive to mechanical impact. Do not puncture container. Contents under pressure. Do not expose to heat or store above 120°F (49°C).

6. ACCIDENTAL RELEASE MEASURES

Small Spill: Eliminate all ignition sources. Ensure adequate ventilation. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly.

Environmental Precautions

Water Spill: Do not flush to sewer.

Land Spill: Avoid runoff into storm sewers and ditches which lead to waterways.

Special Protective Equipment: Clean up spills immediately, observing precautions in Protective Equipment section 8.

7. HANDLING AND STORAGE

General Procedures: Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids. Ensure thorough ventilation of stores and work areas.

Handling: Contents under pressure. Do not expose to heat or store above 120°F (49°C). Use only in a well ventilated area. Do not use in the presence of open flame or spark. Do not puncture container. Do not breath vapors or spray mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Storage: Keep away from heat and flame. Store in a cool dry place. Container may explode if heated. Do not incinerate.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

SSGC SPRAY GUN PAINT REMOVER, aerosol

| OSHA / WHMIS 2015 HAZARDOUS COMPONENTS | | | | |
|--|------------------------------|------|--------|-------------------|
| Chemical Name | Occupational Exposure Limits | | | |
| | Type | | ppm | mg/m ³ |
| acetone | OSHA PEL | TWA | 1000 | 2400 |
| | ACGIH TLV | TWA | 500 | 1188 |
| | | STEL | 750 | 1782 |
| | NIOSH REL | TWA | 250 | 590 |
| propane | OSHA PEL | TWA | 1000 | 1800 |
| | ACGIH TLV | TWA | 1000 | -- |
| | NIOSH REL | TWA | 1000 | 1800 |
| methanol | OSHA PEL | TWA | 200 | 260 |
| | ACGIH TLV | TWA | 200 | 262 |
| | | STEL | 250 | 328 |
| | NIOSH REL | TWA | 200 | 260 |
| STEL | | 250 | 325 | |
| isobutane | ACGIH TLV | STEL | 1000 | -- |
| | NIOSH REL | TWA | 800 | 1900 |
| 2-(2-ethoxyethoxy)ethanol | Canada-Ontario | TWA | 30 | 165 |
| | Germany (DFG) | TWA | [1] | 50 [1] |
| | | STEL | [1] | 100 [1] |
| methyl ethyl ketone | NIOSH REL | TWA | 200 | 590 |
| | | STEL | 300 | 885 |
| | ACGIH TLV | TWA | 200 | -- |
| | | STEL | 300 | -- |
| OSHA PEL | TWA | 200 | 590 | |
| light aromatic solvent naphtha (petroleum) | Supplier OEL | TWA | 19 | 100 |
| 2-methoxy-1-methylethyl acetate | USA OEL | - | -- [2] | -- [2] |
| | EU OEL | TWA | 50 | 275 |
| STEL | | 100 | 550 | |
| xylene, mixed isomers | OSHA PEL | TWA | 100 | 435 |
| | ACGIH TLV | TWA | 100 | 434 |
| | | STEL | 150 | 651 |
| | NIOSH REL | TWA | 100 | 435 |
| STEL | | 150 | 655 | |
| ethylbenzene | OSHA PEL | TWA | 100 | 435 |
| | ACGIH TLV | TWA | 20 | 87 |
| | NIOSH REL | TWA | 100 | 435 |
| | | STEL | 125 | 545 |

SSGC SPRAY GUN PAINT REMOVER, aerosol

Footnotes:

1. Inhalable fraction and vapor.
2. This material does not have established exposure limits in the USA under OSHA, NIOSH, ACGIH.

Engineering Controls: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Personal Protective Equipment

Eyes and Face: Wear safety glasses with side shields (or goggles). Contact lenses should not be worn when working with this product. Eye wash fountains should be readily available to areas of use and handling.

Skin Contact: Wear chemical resistant gloves.

Respiratory: In case of insufficient ventilation, wear suitable respiratory equipment. NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protective Clothing: Wear protective clothing as necessary to prevent contact.

Work Hygienic Practices: Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-------------------------------|--|
| Physical State | : Liquid, without aerosol propellants |
| Odor | : Ketone |
| Odor Threshold | : No data available. |
| Appearance | : Aerosol |
| Color | : Clear, colourless |
| pH | : No data available. |
| % Volatiles | : 100% w/w |
| Flash Point and Method | : -18°C Setafash Closed Cup, acetone [lowest known value of aerosol concentrate] |
| Flammable Limits | : 1.0 to 12.8 |

Notes: Based on data for acetone

Autoignition Temperature : 480°C (896°F)

Notes: Based on data for acetone [lowest known value of aerosol concentrate]

| | |
|----------------------------|--|
| Vapor Pressure | : 55 - 70 psig at 25°C |
| Vapor Density | : > 1 (air = 1) |
| Boiling Point | : 56°C (acetone) [lowest known value of aerosol concentrate] |
| Freezing Point | : No data available. |
| Melting Point | : No data available. |
| Solubility in Water | : Partial |

Evaporation Rate
(n-butyl acetate = 1) : > 1

Density : 0.805 - 0.815 g/ml at 20°C

Notes: An estimate for the aerosol concentrate density

Viscosity : < 10 cps at 25°C

SSGC SPRAY GUN PAINT REMOVER, aerosol

VOC Content : 49 - 50% w/w (< 365 g/l), less exempts

Oxidizing Properties : None

Comments:

Flammability Statement:

The flammability of an aerosol is determined by its flame extension and/or flashback.

Flammability: Yes
Aerosol Flame Projection: > 45 cm but < 100 cm
Flashback: Yes
Calculated Aerosol Chemical Heat of Combustion, kJ/g 30 to 32

VOC Compliance Statement

Total Volatiles: 100% w/w (< 730 g/l)
VOC Content: 49 to 50% w/w
< 365 g/l (< 3.05 lb/gal), less exempt
Density: 0.725 ± 0.005 g/ml
Exempt Content: 50 to 51% w/w

VOC Regulation: Consumer Product Regulations – CARB-California

Product Category: Paint Remover or Stripper

The product VOC content meets the current 50% w/w limit under the CARB Consumer Product Regulations for Paint Remover or Stripper.

Restrictions from Sale: Yes

The definition of aerosol paint remover/strippler used for cleaning coating application equipment such as spray guns in Auto Refinish shops has been re-defined in several CA (California) Auto Refinish district rules to be a surface cleaner subject to a 25 g/l maximum VOC content requirement.

This product is NOT allowed for use in Auto Refinish operations in the following CA (California) districts:

Sacramento Metropolitan AQMD
San Diego County APCD
San Joaquin Valley Unified APCD

Check your area/application for compliance before using this product.

10. STABILITY AND REACTIVITY

Reactive Hazard : No

Hazardous Polymerization: Not expected to occur.

Stability: Stable under normal conditions of use and storage.

Conditions to Avoid: Keep away from flames and any object that sparks. Container may expode if heated.

Possibility of Hazardous Reactions: Strong exothermic reaction with strong oxidants and strong acids.

Hazardous Decomposition Products: By fire and high heat: Carbon monoxide, Carbon dioxide and other undetermined compounds.

Incompatible Materials: Strong oxidizing agents and strong bases.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

SSGC SPRAY GUN PAINT REMOVER, aerosol

| Chemical Name | Oral LD₅₀ mg/kg (rat) | Dermal LD₅₀ mg/kg (rabbit) | Inhalation LC₅₀ mg/l |
|---|--|--|---|
| acetone | 8400 5250(mouse) 5300(rabbit) | >15,700 | 50.1(rat;8h) 44.0(mouse;4h) |
| propane | Not Applicable | Not Applicable | >800,000 ppm (rat,15m) [>1443 mg/L] |
| methanol | 6200(rat) 5630(rat) 7300(mouse) | 15,800 | 83.9(rat;4h) |
| isobutane | Not Applicable | Not Applicable | 658(rat;4h) 570,000 ppm (rat;15m) 680(mouse;2h) |
| 2-(2-ethoxyethoxy)ethanol | 5900 - 6100 7300 6439 5490 | 8476 4200 | >5.24(rat;4h) (aerosol) |
| methyl ethyl ketone | 3400(rat) 2900(rat) 5520(rat) 3140(mouse) | >8000 | 34.5(rat;4h) [11,700 ppm] >5000 ppm (rat;6h) |
| light aromatic solvent naphtha (petroleum) | 3592 | > 3160 | >6.19(rat;4h) (no deaths; saturated vapor) >76.3(rat;4h) |
| 2-methoxy-1-methylethyl acetate | >10,000 8532 13,700 | >5000(rat) >19,400(rbt) | 10.8(rat;3h) 23.5(rat;6h) (no deaths) |
| xylene, mixed isomers | 5400 5251(mouse) 5627(mouse) | 12,180 | 6350 ppm (rat;4h) 6700 ppm (rat;4h) |
| ethylbenzene | 5460 3500 5627(mouse) | 17,800 15,354 | 17.2(rat;4h) 13,367 ppm (rat;2h) |
| cumene | 2910 | > 10,000 | 41.6(rat;1h) |

Acute Toxicity - Dermal LD₅₀: Contains: methanol. Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg. Slightly toxic. May be absorbed through the skin in harmful amounts.

Acute Toxicity - Oral LD₅₀: Contains: methanol. Based on available ingredient data, the mixture is classified as: Acute Oral Toxicity, category 4. The calculated ATE is > 300 and ≤ 2000 mg/kg. Poison, May be harmful or cause blindness if swallowed.

Acute Toxicity - Inhalation LC₅₀: Contains: methanol. Based on available ingredient data, the mixture is classified as: Acute Inhalation Toxicity, category 4. The calculated ATE is >10 and ≤ 20 mg/l/4h (vapours). High vapor or spray mist concentrations may be harmful if inhaled. High vapor concentrations can be encountered in confined spaces and/or under conditions of poor ventilation.

Notes: <5 % of the mixture consists of an ingredient or ingredients of unknown acute toxicity. No additional toxicology information is available for this product itself. (See Component Toxicity Information).

Primary Routes of Entry:

Eye contact. Inhalation. Skin contact. Ingestion.

SSGC SPRAY GUN PAINT REMOVER, aerosol

Skin Irritation / Corrosion: Based on available data, the classification criteria for skin irritation are not met for this mixture. Substance does not generally irritate and is only mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Eye Irritation / Serious Eye Damage: Contains: acetone and methyl ethyl ketone. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as eye irritant, category 2). Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Respiratory / Skin Sensitizer: Based on available data, the classification criteria for respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a respiratory sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a respiratory sensitizer, sub-category 1B).

Based on available data, the classification criteria for skin sensitization are not met for this mixture (< 0.1% ingredients classified as a skin sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a skin sensitizer, sub-category 1B).

Germ Cell Mutagenicity: Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as Germ Cell Mutagen, category 2).

Carcinogenicity

| Chemical Name | NTP status | IARC status | OSHA status | Other |
|--|------------|-------------|-------------|---------------|
| acetone | -- | -- | -- | A4 (ACGIH) |
| propane | -- | -- | -- | -- |
| methanol | -- | -- | -- | -- |
| isobutane | -- | -- | -- | -- |
| 2-(2-ethoxyethoxy)ethanol | -- | -- | -- | -- |
| methyl ethyl ketone | -- | -- | -- | -- |
| light aromatic solvent naphtha (petroleum) | -- | -- | -- | -- |
| 2-methoxy-1-methylethyl acetate | -- | -- | -- | -- |
| xylene, mixed isomers | -- | 3 | -- | -- |
| ethylbenzene | -- | 2B | -- | A3 (ACGIH) |
| cumene | R | 2B | -- | -- |

Notes: ethylbenzene is listed as Group 2B (possibly carcinogenic to humans) by IARC. The mixture is classified as: Carcinogenicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ($\geq 0.1\%$ ingredients classified as a Carcinogen, category 2).

Reproductive Toxicity: Based on available data, the classification criteria for Reproductive Toxicity are not met for this mixture (< 0.1% ingredients classified as Reproductive Toxicity, category 1 or 2).

Specific Target Organ Toxicity - Single Exposure: Contains: methanol. The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 1, based on ingredient data using the applicable cut-off/concentration limits ($\geq 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 1). May cause damage to eyes and optic nerve.

Contains: acetone, methyl ethyl ketone and light aromatic solvent naphtha (petroleum). The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 3, based on summation of ingredient data using the applicable cut-off/concentration limits ($\geq 20\%$ summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3 [Narcotic Effects]). Can cause central nervous system depression (including unconsciousness). High vapor concentrations may cause drowsiness. May cause headaches and dizziness.

Specific Target Organ Toxicity - Repeated Exposure: Contains: xylene, mixed isomers and ethylbenzene. The mixture is classified as: Specific Target Organ Toxicity - Repeated Exposure, category 2, based on ingredient data

SSGC SPRAY GUN PAINT REMOVER, aerosol

using the applicable cut-off/concentration limits ($\geq 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 2). Prolonged inhalation may be harmful. Chronic exposure to organic solvents such as Xylene and Ethylbenzene have been associated with various neurotoxic effects including permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability, and loss of coordination.

Aspiration Hazard: Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture ($< 10\%$ ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity $> 20.5 \text{ mm}^2/\text{s}$ at $40 \text{ }^\circ\text{C}$).

12. ECOLOGICAL INFORMATION

Environmental Data: No data available.

Ecotoxicological Information: No data available.

Bioaccumulation/Accumulation: No data available.

Distribution: No data available.

Aquatic Toxicity (Acute): No data available.

Chemical Fate Information: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal Method: Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

Product Disposal: When container is empty, press button to release all pressure, then dispose of container and unused contents in accordance with Local, Provincial/State and Federal regulations.

14. TRANSPORT INFORMATION

DOT (Department of Transportation)

Proper Shipping Name : AEROSOLS

Primary Hazard Class/Division: 2.1

UN/NA Number : 1950

Packing Group : N/AP

Label : Class 2.1, Flammable Gases

Other Shipping Information:

With an inner packaging $< 1.0 \text{ L}$, this product may be shipped as a Limited Quantity as per DOT 173.306.

Vessel (IMO/IMDG)

Shipping Name : AEROSOLS

UN/NA Number : 1950

Primary Hazard Class/Division: 2.1

Packing Group : N/AP

Marine Pollutant : None

Label : Class 2.1, Flammable Gases

Note: With an inner packaging $< 1.0 \text{ L}$, this product may be shipped as a Limited Quantity.

Canadian Transportation of Dangerous Goods Regulations

Shipping Name : AEROSOLS

UN/NA Number : 1950

SSGC SPRAY GUN PAINT REMOVER, aerosol

Primary Hazard Class/Division: 2.1

Packing Group : N/AP

Label : Class 2.1, Flammable Gases

TDG Note:

For products with an inner packaging < 1.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

15. REGULATORY INFORMATION**UNITED STATES****SARA Section 311/312 Hazard Categories****311/312 HEALTH HAZARDS:** Acute Toxicity (Inhalation), Acute Toxicity (Oral), Carcinogenicity, Eye Irritation, Narcotic Effects, Simple Asphyxiants, Target Organ Toxicity (Repeated exposure), Target Organ Toxicity (Single exposure)**311/312 Physical Hazards:** Flammable Aerosols, Gases Under Pressure**EPCRA Section 313 Toxic Chemicals**

| Chemical Name | Wt. % | CAS number |
|-----------------------|-------------|------------|
| methanol | 10.5 - 11.5 | 67-56-1 |
| xylene, mixed isomers | 2.2 - 2.6 | 1330-20-7 |

EPCRA Section 302 Extremely Hazardous Substances**EPCRA Status:**

This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

CERCLA Hazardous Substances and Reportable Quantities (RQ)

| Chemical Name | Wt. % | RQ |
|-----------------------|-------------|-------|
| acetone | 50 - 51 | 5,000 |
| methanol | 10.5 - 11.5 | 5,000 |
| methyl ethyl ketone | 3 - 4 | 5,000 |
| xylene, mixed isomers | 2.2 - 2.6 | 100 |
| ethylbenzene | 0.5 - 0.7 | 1,000 |
| cumene | < 0.1 | 5,000 |

TSCA (The Toxic Substances Control Act)**TSCA Status:**

All components are included or are otherwise exempt from inclusion on this inventory.

CAA 112(b) - Hazardous Air Pollutants

| Chemical Name | Wt. % | CAS number |
|-----------------------|-------------|------------|
| methanol | 10.5 - 11.5 | 67-56-1 |
| xylene, mixed isomers | 2.2 - 2.6 | 1330-20-7 |
| ethylbenzene | 0.5 - 0.7 | 100-41-4 |

CAA 112(r) - List of Substances for Accidental Release Prevention:

SSGC SPRAY GUN PAINT REMOVER, aerosol

This product contains the following chemicals subject to CAA 112(r).

| Name | CAS No. | Threshold Qty (TQ) |
|---------|---------|--------------------|
| Propane | 74-98-6 | 10,000 |
| Butane | 75-28-5 | 10,000 |

California Proposition 65:

 **WARNING:** This product can expose you to chemicals including the chemical(s) listed below, which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Chemical Name | Wt. % | Listed |
|---------------|-------------|--------------------------|
| methanol | 10.5 - 11.5 | ● Developmental Toxicity |
| ethylbenzene | 0.5 - 0.7 | ● Cancer |
| cumene | < 0.1 | ● Cancer |

OSHA Hazard Communication Standard (29 CFR 1910.1200):

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

CANADA

WHMIS Hazard Symbol and Classification

See Section 2 for details.

WHMIS Regulatory Status:

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

WHMIS Classification:

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

CEPA - National Pollutant Release Inventory (NPRI):

SSGC SPRAY GUN PAINT REMOVER, aerosol

| Name | CAS No. | NPRI Part No. |
|--|------------|---------------|
| methanol | 67-56-1 | 1A, 5 (VOC) |
| 2-methoxy-1-methylethyl acetate | 108-65-6 | 5 (VOC) |
| methyl ethyl ketone | 78-93-3 | 1A, 5 (VOC) |
| light aromatic solvent naphtha (petroleum) | 64742-95-6 | 5 (VOC) |
| xylene, mixed isomers | 1330-20-7 | 1A, 5 (VOC) |
| ethylbenzene | 100-41-4 | 1A, 5 (VOC) |
| propane | 74-98-6 | 5 (VOC) |
| isobutane | 75-28-5 | 5 (VOC) |

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):

All components are included or are otherwise exempt from inclusion on this inventory.

Comments VOC Content -- See section 9.

16. OTHER INFORMATION

Reason for Issue: The Safety Data Sheet was updated.

Approved By: Jim Gordon **Title:** R&D Chemist

Prepared By : Regulatory Compliance


Date Revised: 07/14/2020

Information Contact: 905-670-5411

Revision Summary: This MSDS replaces the 05/29/2020 MSDS.

HMIS RATING

| | | |
|----------------------------|---|----------|
| HEALTH | * | 2 |
| FLAMMABILITY | | 4 |
| PHYSICAL HAZARD | | 0 |
| PERSONAL PROTECTION | | G |

NFPA CODES

NFPA 30 / 30B Storage Classification: Level 3 Aerosol

Manufacturer Supplemental Notes: None

Data Sources: Not Available

Additional SDS Information: N/AV Not Available

N/AP Not Applicable

ND Not yet determined

ACGIH American Conference of Governmental Industrial Hygienists

CAA The Clean Air Act

CCCR The Consumer Chemicals and Containers Regulations

CEPA The Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

SSGC SPRAY GUN PAINT REMOVER, aerosol

EPCRA The Emergency Planning and Community Right-To-Know Act
IARC International Agency for Research on Cancer
MSHA Mine Safety and Health Administration
NIOSH National Institute for Occupational Safety and Health
NTP National Toxicology Program
OSHA The Occupational Safety and Health Administration
SARA The Superfund Amendments and Reauthorization Act
WHMIS Workplace Hazardous Materials Information System

General Statements: None

Comments: None

Manufacturer Disclaimer: The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.